



World-class industrial high pressure grease pumps with guaranteed performance and hassle free operation

Recommended use with light and self collapsing grease up to NLGI No. 2

All metal construction, fully CNC machined with hardened wear resistant moving parts

Fitted with strainer at suction tube inlet for clean grease to the bearing

Optional trolley available

Specification:

Working air pressure	2 to 10bar (30 to 150psi)	Grease Output (NLGI No.2)	1.10 kg/min (2.42lbs/min)
Maximum air pressure	10bar (150psi)	Drum cover diameter	284mm
Maximum outlet pressure	500bar (7500psi)	Follower plate OD steel end	230mm
Air inlet connection	1/4" BSP (F)	Follower plate OD plate	257mm
Pump outlet connection	1/4" BSP (F)	Noise Level	81db
Air consumption	230 ltr / min (61gpm)		

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865

Sohar - 9133 2946, Salalah - 7193 6778

Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668,
9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opalte.com Opal Tools & Equipment - Oman opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112,
Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com