



In Ground Scissor Lift SXJS 3018



Features:

1. High rigidity, good synchronization performance.
 2. In-ground installation, the minimum height is 340mm, save space, beautiful and durable.
 3. Imported hydraulic seals, the whole system is stable, and with hydraulic and mechanical protection, safe and reliable;
 4. Platform is adjustable, standard configuration is double side extended(Maximum length 2060mm), Model SXJS3018 is single sides extended (Maximum length 1760mm).
 5. Lifting height up to 1800mm, suitable for taller persons operation.
 6. When the lift lower, buzzer will alarm to ensure the safety of personal.
 7. Limited switch can keep equipment long-term security and stability, prolong the service life.
- The overall design is very suitable for dismounting tires, chassis repair, oil change and fast repair maintenance, preflight

Specification:

Lifting Capacity	3.0T (6600LB)	Voltage	380/220V
Lifting Height	340+1800mm(13+7 inch)	N.W	0.68T (1499LB)
System Pressure	25 Mpa	MIN. Height	340mm (13 inch)
Air Pressure	0.4-0.8Mpa	Platform Length	1660-2060mm (65-81 inch)
Motor Power	2.2KW		

Showroom



Tools & Equipment

Way No 7721, Road No 5, Mabela Industrial Area, Muscat, Oman.

Mabela Showroom: 9396 6865

Sohar - 9133 2946, Salalah - 7193 6778

Nizwa - 7158 3574, Jalan Bani Bu Ali - 9988 2973

9983 3239, 9320 0399, 9897 5620, 9381 9668,
9915 9088, 91788 597, 91742 867, 9386 2790

2246 4851 | **Toll Free: 8000 4321**

www.opalte.com | Opal Tools & Equipment - Oman | opaltoolsandequipment

Head Office



Opal Marketing & Industry LLC

P.O. Box - 273, Ruwi, Postal Code: 112,
Muscat, Oman.

2447 8568, 2447 9986 | Fax: 2447 8566

www.opalgcc.com